

SAFETY DATA SHEET

according to 1907/2006/EC, Article 31

Page 1/4

MDEV650X Majestic Select 650 Rapid Access Developer 15 Gal (20L drum)

Revision 0

Revision date 2013-01-07

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name MDEV650X Majestic Select 650 Rapid Access Developer 15 Gal (20L drum)

1.3. Details of the supplier of the safety data sheet

Company	Champion Photochemistry Sdn Bhd
Address	Lot 28-B Mukim Batu Industrial Area 6 1/2 Miles Jalan Kepong 52000 Kuala Lumpur MALAYSIA
Web	www.championphotochemistry.com
Telephone	+603-6257 2600
Fax	+603-6257 2622


SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

2.1.1. Classification - 1999/45/EC C; R34 Xn; R40-68 Xi; R43
Symbols: C: Corrosive.

Main hazards Causes burns. Limited evidence of a carcinogenic effect. May cause sensitisation by skin contact. Possible risk of irreversible effects.

2.2. Label elements

Symbols	The product is classified in accordance with 67/548/EEC. C: Corrosive. 
Risk phrases	R34 - Causes burns. R40 - Limited evidence of a carcinogenic effect. R43 - May cause sensitisation by skin contact. R68 - Possible risk of irreversible effects.
Safety phrases	S24 - Avoid contact with skin. S26 - In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. S28 - After contact with skin, wash immediately with plenty of. S36/37/39 - Wear suitable protective clothing, gloves and eye/face protection. S45 - In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).

SECTION 3: Composition/information on ingredients

3.2. Mixtures

MDEV650X Majestic Select 650 Rapid Access Developer 15 Gal (20L drum)

Revision 0

Revision date 2013-01-07

3.2. Mixtures

67/548/EEC / 1999/45/EC

Chemical Name	Index No.	CAS No.	EC No.	REACH Registration Number	Conc. (%w/w)	Classification
DI Water		7732-18-5			70 - 80%	
Potassium Carbonate		584-08-7	209-529-3		1 - 10%	Xn; R22 Xi; R37/38
Potassium hydroxide	019-002-00-8	1310-58-3	215-181-3		1 - 10%	Xn; R22 C; R35
Sodium Sulphite Anhydrous		7757-83-7	231-821-4		10 - 20%	
Hydroquinone		123-31-9	204-617-8		1 - 10%	Xn; R22-40-68 Xi; R41-43 N; R50
Potassium Sulfite		10117-38-1	233-321-1		1 - 10%	
Pentasodium DTPA Solution 42%		140-01-2	205-391-3		1 - 10%	C; R35 Xn; R22-40

SECTION 4: First aid measures**4.1. Description of first aid measures**

Inhalation	Inhalation of vapour may cause shortness of breath. Move the exposed person to fresh air. Seek medical attention.
Eye contact	Causes burns. Causes severe inflammation and may damage the cornea. Seek medical attention. Irritating to eyes.
Skin contact	Wash off immediately with plenty of soap and water. Remove contaminated clothing. Seek medical attention if irritation or symptoms persist.
Ingestion	Ingestion causes burns to the respiratory tract. DO NOT INDUCE VOMITING. If swallowed, seek medical advice immediately and show this container or label.

SECTION 5: Firefighting measures**5.1. Extinguishing media**

	Not applicable. This product is not flammable.
--	--

5.2. Special hazards arising from the substance or mixture

	Corrosive. Burning produces irritating, toxic and obnoxious fumes.
--	--

5.3. Advice for firefighters

	Protective equipment. Wear suitable respiratory equipment when necessary. In case of fire and/or explosion do not breathe fumes.
--	--

SECTION 6: Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures**

	Ensure adequate ventilation of the working area. Evacuate personnel to a safe area. Wear suitable protective equipment.
--	---

6.2. Environmental precautions

	Do not allow product to enter drains. Prevent further spillage if safe.
--	---

6.3. Methods and material for containment and cleaning up

	Absorb with inert, absorbent material. Transfer to suitable, labelled containers for disposal. Clean spillage area thoroughly with plenty of water.
--	---

SECTION 7: Handling and storage**7.1. Precautions for safe handling**

	Avoid contact with eyes and skin. Ensure adequate ventilation of the working area.
--	--

7.2. Conditions for safe storage, including any incompatibilities

	Keep in a cool, dry, well ventilated area. Keep containers tightly closed.
--	--

SECTION 8: Exposure controls/personal protection

MDEV650X Majestic Select 650 Rapid Access Developer 15 Gal (20L drum)

Revision 0

Revision date 2013-01-07

8.1. Control parameters

8.1.1. Exposure Limit Values

Hydroquinone	WEL 8-hr limit ppm: - WEL 15 min limit ppm: -	WEL 8-hr limit mg/m3: 0.5 WEL 15 min limit mg/m3: -
Potassium hydroxide	WEL 8-hr limit ppm: - WEL 15 min limit ppm: -	WEL 8-hr limit mg/m3: - WEL 15 min limit mg/m3: 2

8.2. Exposure controls

8.2.1. Appropriate engineering controls	Ensure adequate ventilation of the working area.
8.2.2. Individual protection measures	Wear chemical protective clothing.
Eye / face protection	Approved safety goggles.
Skin protection - Handprotection	Chemical resistant gloves (PVC).
Respiratory protection	Wear: Self-contained breathing apparatus.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

State	Liquid
Colour	Yellow
pH	10.6
Relative density	1.232
Solubility	Soluble in water

SECTION 10: Stability and reactivity

10.2. Chemical stability

	Stable under normal conditions.
--	---------------------------------

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Skin corrosion/irritation	May cause irritation to skin. Prolonged or repeated exposure may cause irritation to skin and mucous membranes.
Repeated or prolonged exposure	May cause allergic reactions in susceptible people. May cause severe irritation to eyes and skin.

11.1.4. Toxicological Information

	No data available
--	-------------------

SECTION 12: Ecological information

12.1. Toxicity

	No data available
	Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

SECTION 13: Disposal considerations

General information

	Dispose of in compliance with all local and national regulations.
--	---

Disposal methods

	Do not empty into drains; dispose of this material and its container in a safe way. Do NOT mix with any other product. Do not empty into drains, dispose of this material and its container at hazardous or special waste collection point.
--	---

MDEV650X Majestic Select 650 Rapid Access Developer 15 Gal (20L drum)

Revision 0

Revision date 2013-01-07

SECTION 14: Transport information**ADR/RID**

The product is not classified as dangerous for carriage.

IMDG

The product is not classified as dangerous for carriage.

IATA

The product is not classified as dangerous for carriage.

SECTION 15: Regulatory information**Further information**

No Significant Hazard.

SECTION 16: Other information**Other information****Text of risk phrases in Section 3**

R22 - Harmful if swallowed.
 R35 - Causes severe burns.
 R37/38 - Irritating to respiratory system and skin.
 R40 - Limited evidence of a carcinogenic effect.
 R41 - Risk of serious damage to eyes.
 R43 - May cause sensitisation by skin contact.
 R50 - Very toxic to aquatic organisms.
 R68 - Possible risk of irreversible effects.

Further information

The information supplied in this Safety Data Sheet is designed only as guidance for the safe use, storage and handling of the product. This information is correct to the best of our knowledge and belief at the date of publication however no guarantee is made to its accuracy. This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any other process.